



CX2510 Series

24.5 HP



1 Power Steering wheel

With hydraulic power steering, you will experience smooth responsive steering that reduces the effort required to make tight turns or repetitive tasks.

4 Illuminated Dashboard

The illuminated dashboard ensures great visibility while working in bright daylight or at night.

The digital gauge shows tachometer, fuel and temperature with warning signs for low fuel and high temperature.

2 Single Lever Joystick

Front end loader work is made easier by the use of a single lever joystick. The lever automatically returns to neutral and the loader stops in place when the joystick is released. A float position allows the bucket free floatation over the ground surface.

3 Powerful HST Transmission with Twin HST Pedal

Heavy-duty HST with two-range transmission(Hi/Low) helps you simply get your job done. CX2510 HST models utilize a two pedal system for forward and reverse with smooth engagement, acceleration and deceleration.



EXPERIENCE THE POWERFUL CX2510



Hi/Low Speed Ranges

The CX features a two range transmission (Hi/Low) to maximize performance and efficiency.

Streamlined Hood Design

Visibility and serviceability are improved for the operator with the streamlined hood design. The vertical opening hood allows for easy access to the air filter, fluid service, fuse box and other major electrical components.



Advanced Air Conditioning System(CAB Model)

The improved Cooling and Heating system will ensure the perfect climate control for comfortable working conditions all year round.



HST Linked Easy Speed

When the HST linked pedal is engaged, the HST pedal and the engine rpm are synchronized. This reduces fuel consumption and simplifies tractor operation for a variety of utility and loader applications.



Manual & HST Transmission

The manual transmission model features 6F/2R speeds. The HST model utilizes a performance proven, heavy-duty HST that delivers power smoothly and efficiently. With the HST drive your hands remain free for steering and implement control.



Stationary PTO

The operator can simply engage the S-PTO switch whenever the operator needs to run PTO other than the seating position



USB and Power Socket

Power and USB sockets come standard to meet a variety of electrical needs.



Foldable ROPS

The standard fold-down roll bar makes it quick and easy to maneuver in low clearance areas.



ISO 9001
NO.954596



ISO 14001
NO.771475



OHSAS 18001
NO.K033008

SPECIFICATIONS

MODEL	CX2510		CX2510N	CX2510H	CX2510CH
	Manual		Manual	HST	HST
ENGINE					
Model	3A165LWH-E			3A165LWH-E2	
Engine Gross Power	HP	24.5			
Rated Revolution	rpm	2,600			
Type	3Cyl., In-line Vertical, Water-cooled 4-cycle diesel engine				
Total Displacement	cc	1,647			
Fuel Tank	l	25			
PTO	Type	Transmission		Live	
	rpm	Rear: 540 / Mid: 2,000(opt.)			
DRIVE TRAIN					
Transmission	Manual		HST		
No. of Speeds	6F2R		-		
Mechanical differential lock	Rear Standard				
Traveling Speed Forward	km/h	1.22-19.07		0-21.74	
Traveling Speed Reverse	km/h	1.51-7.40		0-15.22	
HYDRAULIC SYSTEM					
3 Point Lift Control Type	Position				
Implement Pump	l/min	26			
Power Steering Pump	l/min	16.9			
Total Hydraulic Flow	l/min	42.9			
3-point Hitch Type	Category I				
Lower Link Type	Ball				
Lift capacity at lift point	kg.f	739			
Lift capacity at 24 in. behind lift point	kg.f	546			
No. of standard remote valves (Rear)	2port				
TIRE SIZE					
AG. Tire Front	7-12/6				
AG. Tire Rear	11.2-16/6				
Turf Tire Front	23x8.5-12				
Turf Tire Rear	33x12.5-16.5				
Industrial Tire Front	23x8.5-12				
Industrial Tire Rear	12-16.5				
DIMENSIONS					
Overall Length (Includes 3-pt Hitch)	mm	2,790		2,826	
Overall Width (Minimum Tread)	mm	1,185			
Tread Width Front 4WD	mm	969			
Tread Width Rear	mm	935			
Overall Height(with ROPS)	mm	2,335	2,048	2,335	-
Wheel Base	mm	1,520			
Ground(Crop) Clearance	mm	340			
Weight with ROPS	kg.f	1,042	1,070	1,042	-
Weight with CABIN	kg.f	-	-	-	1,272

* NOTE : Specifications and design are subject to change without notice.

STANDARD EQUIPMENT


- 2-Port Double Acting Valve
- 7-Pin Socket
- Rear View Mirror
- Hydraulic Power Steering
- Adjustable Suspension Seat
- Joystick Lever with Mid Mount Valve (CX2510N: Option)
- Cruise Control (HST Model)
- Rear Differential Lock
- Towing Hook
- Stationary PTO
- Parking Brake
- Air Conditioning System(CX2510CH)

OPTIONAL EQUIPMENT

- AG Tire Set
- Turf Tire Set
- Industrial Tire Set
- Mid PTO
- Front Weights
- Rear Weights
- Working Lamp
- Sun Canopy

ATTACHMENTS

- Front Loader



Loader Specifications

MODEL	KL2510
A	Maximum Lift Height to Pivot Pin 2,230 mm
B	Maximum Lift Height Under Level Bucket 2,141 mm
C	Clearance w/ Bucket Dumped 1,706 mm
D	Reach at Maximum Lift Height 800 mm
E	Maximum Dump Angle 53°
F	Reach w/ Bucket on Ground 1,498 mm
G	Maximum Rollback Angle 33°
H	Digging Depth 99 mm
J	Overall Height in Carry Position 1,016 mm
L	Bucket Depth 498 mm
M	Bucket Height 411 mm
N	Bucket Length 632 mm
Lift Capacity to Maximum Height 480 kg	
Breakout Force 835 kg	
Relief Valve Setting (Loader Control Valve) 2,275 psi	
Rated Flow (Tractor System) 7.66 gpm	
Bucket Size 1,270 mm	
Bucket Capacity (Rated / Heaped) 0.12 / 0.19m3	



Daedong Kioti Europe B.V.
Koerilenstraat 2-6, 3199 LR, Maasvlakte
Rotterdam The Netherlands
Tel +31(0)181-35 30 24
Website www.kioti.eu

Dealer Imprint Area

LIT-CX10-ALL1